

CONDUDAN



Aqueous Epoxy Based Conductive Coating System

DESCRIPTION

CONDUDAN is two component waterborne epoxy based anti-static coating system for use as conductive base coat in conjunction with epoxy based antistatic flooring system or with any other ESD coating / flooring system.

It is specially formulated with unique conductive fillers for use on surfaces to provide uniform electrical conductivity and make it suitable for electrostatic discharge, static disseminating and spark proof floor lining systems.

ADVANTAGES

- V.O.C free
- Excellent anti-static property
- Water based - Environmental friendly
- Seamless system
- Maintains electrical conductivity over the useful life of epoxy flooring system
- Low odour during application
- Extended pot life and fast drying

USES

CONDUDAN is used to provide a conductivity layer for subsequent anti-static floor toppings or coatings or ESD systems, in areas:

- Air-traffic control rooms and flight deck on ships
- Ammunitions and pyrotechnics manufacturing units
- Optical lenses and photographic production units
- Medical equipment units
- Electronic production areas and assembly shops
- Nuclear power plants
- LPG bottling and filling plant
- Areas handling/storing flammable/explosive goods

APPLICATION INSTRUCTIONS

SURFACE PREPARATION

The surfaces receiving **CONDUDAN** must be sound, clean, dry, and free from cracks, loose particles and foreign materials which is detrimental to adhesion of **CONDUDAN**.

SURFACE PRIMING

In areas where anti-static flooring or ESD floorings is to be laid, prior to application of conductive coat **CONDUDAN**, the substrate must be insulated by applying non-conductive epoxy primer **DANOFLOOR PRIMER EP @ 6 to 8 m²/Kg.**, on well prepared substrate covering the entire area uniformly. (Refer TDS of **DANOPRIMER EP** for details).

Allow the primer to dry. On very absorbent or porous surface, it is necessary to apply second coat of primer.

CONNECTION TO EARTHING SYSTEM

Over the dry primer, self-adhesive copper tape is laid and connected to earthing system by providing a copper plate at the junctions and connecting the tape to the horizontal face of plate, the vertical end of plate is connected to earthen wire thereby completing the earthing system. (Refer TDS of **DANOFLOOR SL AS** for details).

CONDUCTIVE COAT

CONDUDAN is supplied as pre-weighed two components, ready to use at site. The components of **CONDUDAN** shall be mixed by taking **CONDUDAN Resin** component in a clean container followed by addition and gradual mixing of **CONDUDAN Hardener** component using slow speed heavy duty electric stirrer to achieve homogeneous and uniform mix.

The prepared mix of **CONDUDAN** is applied by brush or roller or trowel @8 to 10 m²/Kg., covering the entire area uniformly.

Water up to 10% can be added to the mix to maintain the application consistency of conductive base coat.

When used as a moisture-resistant barrier on concrete and masonry surfaces, **CONDUDAN** can be directly applied on concrete surface.

Allow the conductive coat to dry before applying subsequent layers.

After application, **CONDUDAN** should be top coated with anti-static floor topping or coating or ESD system.

CLEANING

Immediately after application of **CONDUDAN**, use clean water for cleaning application tools.

APPLICATION DATA

Mix Ratio PWB Resin: Hardener	100 : 150
Pot Life @30°C	Approximate 1 Hour
Curing Schedule	24 to 48 Hour (Hard Dry)
Coverage* per Pack	20 to 25 m ² per coat

Disclaimer: The technical information, and, in particular, the recommendations relating to the application and end-use of Tiki Tar Danosa (TIKIDAN) products, are given in good faith based on TIKIDAN's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with TIKIDAN's recommendations. The information herein is of a general nature and no assumption can be made as to a product's suitability for a particular use or application and no warranty in respect of merchantability or of fitness for a particular purpose can be inferred from this information. The user alone is fully responsible for the product's suitability for the intended application and purpose. TIKIDAN reserves the right to change the properties of its products.

Note: Field service where provided does not constitute supervisory responsibility. Suggestions made by TIKIDAN either orally or in writing may be followed, modified or rejected by the owner, engineer or contractor since they, and not TIKIDAN, are responsible for carrying out procedures appropriate to a specific application. TIKIDAN reserves the right to amend the composition of its material and consequently their prices, without prior notice. For this reason, all orders will be accepted only in accordance with the conditions and technical specifications in force at the date of order. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

TIKITAR DANOSA (INDIA) PRIVATE LIMITED

Tiki Tar Estate, Village Road, Bhandup (W), Mumbai - 400 078,
Maharashtra, India. T: +91 22 4126 6699
E: info@tikidan.in | W: www.tikidan.in

*Coverage is approximate and it depends upon the site conditions and surface porosity at the time of application.

PROPERTIES OF APPLIED PRODUCT

Properties*	Value	Test Standard
Tensile Strength	>18 N/mm ²	ISO 527
Electrical Conductivity	500 to 2000 Ω	ASTM F150-06

*Properties tested under laboratory condition for specimens cured for 15days @30°C. Properties may vary based on actual site conditions.

STORAGE

CONDUDAN must be stored above 5°C. Store under the shed & protect from extremes of temperature, heat, direct sunlight and children.

SUPPLY

CONDUDAN is supplied in 2.5 Kg, pack. It has a shelf life of 6 months when stored under the covered shed in sealed condition.

Packing: 2.5 Kg.

Resin	Hardener
1 Kg.	1.50 Kg.

SAFETY PRECAUTIONS

As with all chemical products, care should be taken during use and storage of **CONDUDAN**.

VERSION: R1, 201901

